HYDRA RAM®

ADVANCED DEMOLITION EQUIPMENT

RS-SERIES

HYDRAULIC BREAKERS

RANGE FROM 1700 TO 4200 KG

5 MODELS FOR CARRIERS FROM 18 TO 60 TONS

HYDRA RAM®

ADVANCED DEMOLITION EQUIPMENT

SPECIFICATIONS			
MODEL	**RS-17**	**RS-22**	**RS-27**
WEIGHT (kg)	1700	2200	2700
OILFLOW (l/pm)	120~160	160~230	170~240
PRESSURE (bar)	145	145	150
BLOW FREQUENCY (b/pm)	350~500	350~500	300~450
TOOL DIAMETER (mm)	130	140	155
EXCAVATOR (t)	18 ~ 24	22 ~ 30	28 ~ 35
ENERGY (j)	4500	6600	7950
MODEL	**RS-32**	**RS-42**	
WEIGHT (kg)	3300	4200	
OILFLOW (l/pm)	190~250	220~350	
PRESSURE (bar)	155	155	
BLOW FREQUENCY (b/pm)	250~400	200~350	
TOOL DIAMETER (mm)	170	180	
EXCAVATOR (t)	33 ~ 45	40 ~ 60	
ENERGY (j)	9300	13800	

*** Above specifications are subject to change without prior notice

(DEALER)

HYDRA RAM®
ADVANCED DEMOLITION EQUIPMENT

HYDRARAM b.v.
Meander 7
NL 9231DB SURHUISTERVEEN
The Netherlands

tel. +31 512-365981
fax.+31 512-365761
www.hydraram.com
info@hydraram.com

*SPECIFICATIONS IN THIS BROCHURE ARE SUBJECT TO CHANGE WITHOUT NOTICE