

HYDRA RAM®

ADVANCED DEMOLITION EQUIPMENT



XG-SERIES

HYDRAULIC ROCK BREAKERS

FULL RANGE FROM 90 TO 4100 KG

12 MODELS FOR CARRIERS FROM 0,8 TO 64 TONS

HYDRA RAM®

ADVANCED DEMOLITION EQUIPMENT

LIGHT RANGE					
MODEL		XG-1S	XG-2S	XG-3S	XG-4S
WEIGHT	(kg)	90	150	290	380
OILFLOW	(l/pm)	15-20	25-40	30-60	40-70
PRESSURE	(bar)	90-120	90-120	110-140	120-150
BLOWS	(b/pm)	625-1500	600-1100	500-1000	500-900
TOOL	(mm)	48mm	53mm	68mm	75mm
EXCAVATOR	(t)	0.8-2.0	2.0-3.5	3.0-5.0	5.0-8.0
ENERGY	(j)	234	390	740	980
MEDIUM RANGE					
MODEL		XG-6S	XG-10S	XG-15S	XG-20S
WEIGHT	(kg)	600	900	1350	1700
OILFLOW	(l/pm)	50-85	80-110	90-120	120-150
PRESSURE	(bar)	130-160	150-170	150-170	160-180
BLOWS	(b/pm)	400-800	350-700	350-600	360-600
TOOL	(mm)	85mm	100mm	120mm	135mm
EXCAVATOR	(t)	7.0-1.4	10.1-16	14-19	18-26
ENERGY	(j)	1460	2200	3400	4400
HEAVY RANGE					
MODEL		XG-30S	XG-40S	XG-50S	XG-70S
WEIGHT	(kg)	2300	2850	3600	4100
OILFLOW	(l/pm)	160-200	200-260	220-290	250-350
PRESSURE	(bar)	160-185	170-190	170-190	170-190
BLOWS	(b/pm)	300-450	250-400	250-400	200-350
TOOL	(mm)	150mm	155mm	175mm	180mm
EXCAVATOR	(t)	24-32	28-36	36-50	45-64
ENERGY	(j)	6400	7800	9100	12400

(DEALER)

HYDRA  RAM®
ADVANCED DEMOLITION EQUIPMENT

HYDRARAM b.v.
Meander 7
NL 9231DB SURHUISTERVEEN
The Netherlands

tel. +31 512-365981
fax. +31 512-365761
www.hydraram.com
info@hydraram.com

*SPECIFICATIONS IN THIS BROCHURE ARE SUBJECT TO CHANGE WITHOUT NOTICE